

Specifications MP512

This page uses Adobe Flash. [Click here to install it.](#)

Native Resolution	SVGA (800 x 600)
Projection System	DLP™ technology by Texas Instruments®
Brightness	2200 ANSI lumens
Lamp	185W, 3000/4000 hours(Normal/Eco)
Contrast Ratio	2500:1 (Full on/Full off)
Weight	4.9 lbs (2.2 kg)
Noise Level	31/26 dB (Normal/Economic mode)
Resolution Support	VGA(640 x 480) to SXGA(1280 x 1024)
Dimensions	10 x 3.5 x 8.4 inches (255 x 90 x 214 mm)
Image Size	25" to 300"
Throw Ratio	2.0:1
Throw Distance	25" to 300"
Zoom Ratio	Fixed
Lens	F= 2.6 f=22mm
Display Color	Full 16.7 million color palette
Aspect Ratio	4:3 Native, 16:9 Selectable
Horizontal Frequency	31 - 82 kHz
Vertical Scan Rate	48 - 85 Hz
Projection Position	Front/Rear, Table/Ceiling
Input Terminals	PC : Analog RGB: D-sub 15 pin x 1 A/V : Component Video: D-sub 15 pin (Shared with Analog RGB connector) S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1
Output Terminals	PC :D-sub 15 pin X 1
Video Compatibility	NTSC, PAL, SECAM
Auto Switching Power Supply	100 to 240 VAC, 50 to 60 Hz
Power Consumption	Max 280W, Standby Max 5W
On-Screen Display Language	English/ French/ German/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese / Thai/ Polish
Preset Modes/ Application Modes	PC Input: Dynamic Mode Presentation Mode sRGB Cinema Mode User 1 Mode User 2 Mode A/V Input : Dynamic Mode Standard Mode Cinema Mode User 1 Mode User 2 Mode
Functions	BrilliantColor™ 3D Color Management Wall color correction

	Quick Auto Search Time Controller Presentation Timer Closed Captioning(CC1~CC4) Standby D-Sub Output Baud Rate Change Resolution Reminder Panel Key Lock "Q?" Hot Key for FAQ Power On/Off Ring Tone 11 sets of Picture Mode Auto Phase Adjustment Blank @ ECO mode Quick Cooling Auto Off Security Password High Altitude Mode
Product Color	Black
Accessories (Standard)	Quick start guide Manual CD Remote control w/battery VGA cable PWR cord
Accessories (Optional)	Ceiling Mounting Kit Presentation Plus Spare Lamp Kit